


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

| | |
|--|--|
|  | <p style="text-align: center;"><u>IEK TERMOCONTRACTIBIL PKVTPBE 5X150/240 WITH PVC ISOLATION 1KV</u></p> <p>PKV(N)tpbe-1 and PKVtpbe-1 heat-shrink sleeves are designed for termination of aluminum or copper conductors of cables with plastic, rubber and polyethylene insulation with armor or shield for voltages up to 1 kV: AVBbShv-1, VBbShv-1, AVVB-1, AVVBG-1, VVB-1, VVBG-1, APvBbShv-1, PvBbShv-1, VVGE, AVVGE, PvVGE, APvVGE, their equivalents and versions. The product's range is developed for 1-, 2-, 3-, 4- and 5-core cables. The sleeve can be used with armored and shielded cables and includes a kit of soldered or not soldered grounding options. The soldered grounding kit contains constant force springs (CFS) made from high-quality stainless steel AISI 301 with high content of chromium and nickel, that ensure reliable and safe connection of PML grounding bus to cable armor bands.</p> <p>Use of high-quality two-layer heat-shrink materials with adhesive thermomelting coating on inner surfaces of tubes and multiple cable joints ensures perfect tightness of the sleeve construction. Suitable for: EV009707</p> <p>Model: EV004267 Voltage row: EV004258 Nominal cross section: 150...240 Type of insulation material: IEK_V0000184 Installation Type: IEK_V0000187 Complete set: IEK_V0000188 Number of cores wiring: 5 Tip Type: IEK_V0000190 Attachment of the grounding bus to the cable: EV000764 Nominal voltage: 1 Material: IEK_V0000193 Min full shrinkage temperature: 120 Operating temperature range: -45...+50 Shrink rate: EV009535 External grounding bus attachment: IEK_V0000194 Number of conductors: 5 Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/termocontractibil-pkvtpbe-5x150-240-with-pvc-isolation-1kv-310565</p> |
|--|--|