



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 ( primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Banca: BRD IBAN: RO34BRDE441SV13182234410

IEK TERMOCONTRACTIBIL PKVTP 1X16/25 WITH PVC ISOLATION 1KV
PKV(N)tp-1 and PKVtp-1 heat-shrink sleeves are designed for termination of aluminum or copper conductors of cables with plastic, rubber and polyethylene insulation for voltages up to 1 kV: AVVG-1, VVG-1, AVVGz-1, VVGz-1, APvVG-1, PvVG -1, their equivalents and versions.Quick and easy mounting of heat-shrink components using gas torch or high-temperature drying fan. Perfectly leak-tight sleeve design due to: - use of high-quality two-layer heat-shrink materials; - adhesive thermomelting coating on inner surfaces of heat-shrink tubes and multiple cable joints. Wide range of products, with several versions of sleeve supply: without lugs, with bolted lugs having break-out heads, with compression lugs.Suitable for: EV009729 Model: EV004257 Voltage row: EV004258 Nominal cross section: 1625 Type of insulation material: IEK V0000184
Installation Type: IEK_V0000184 Installation Type: IEK_V0000185 Complete set: IEK_V0000188 Number of cores wiring: 1 Tip Type: IEK_V0000189 Nominal voltage: 1 Material: IEK_V0000193 Min full shrinkage temperature: 120 Operating temperature range: -45+50
Operating temperature range. 45150   Shrink rate: EV009535   Number of conductors: 1   Pret: 0,00 lei (TVA inclus)   Detalii online: https://www.materialeelectrice.ro/termocontractibil-pkvtp-1x16-25-with-pvc-isolation-1kv-310637