



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



PKV(N)tp-1 and PKVtp-1 heat-shrink sleeves are designed for termination of aluminum or copper conductors of cables with plastic, rubber and polyethylene insulation for voltages up to 1 kV: AVVG-1, VVG-1, AVVGz-1, VVGz-1, APvVG-1, PvVG -1, their equivalents and versions. Quick and easy mounting of heat-shrink components using gas torch or high-temperature drying fan.

Perfectly leak-tight sleeve design due to:

use of high-quality two-layer heat-shrink materials;

- adhesive thermomelting coating on inner surfaces of heat-shrink tubes and multiple cable joints.

Wide range of products, with several versions of sleeve supply: without lugs, with bolted lugs having break-out heads, with compression lugs. Suitable for: EV009729 Model: EV004267

Voltage row: EV004258 Nominal cross section: 35...50

Type of insulation material: IEK V0000184

Installation Type: IEK V0000185 Complete set: IEK_V0000188 Number of cores wiring: 1 Tip Type: IEK_V0000189
Nominal voltage: 1
Material: IEK_V0000193
Min full shrinkage temperature: 120

Operating temperature range: -45...+50 Shrink rate: EV009535

Number of conductors: 1 Pret: 0,00 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/termocontractibil-pkvtp-1x35-50-withpvc-isolation-1kv-310638