

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK TERMOCONTRACTIBIL PKNTP-10 3X300 WITH PVC ISOLATION

Terminations for cables with 10kV cross-linked polyethylene insulation. Heat shrinkable termination couplings for outdoor installation are designed for termination of three core aluminium and copper cables with cross-linked polyethylene insulation without armor and with copper wire screen for a voltage of 10kV: APvV-10, APvP-10, APvP2g-10, APvPg-10, APvPu-10, APvPu2g-10, APvPug-10, PvV-10, PvP-10, PvP2g-10, PvPg-10, PvPu-10, PvPu2g-10, PvPug-10, their analogues and modifications. Quick and easy installation of heat-shrinkable coupling components using a gas burner or high-temperature hair dryer.

Absolute tightness of the coupling design due to:

- application of high-quality two-layer heat-shrinkable materials;
- hot-melt adhesive layer on the inner surface of heat-shrinkable tubes and gloves.

Equipment without lugs. Suitable for: EV009729

Model: EV004267

Voltage row: EV004261

Nominal cross section: 300

Type of insulation material: IEK_V0000184

Installation Type: IEK_V0000186

Complete set: IEK_V0000188

Number of cores wiring: 3

Tip Type: IEK_V0000190

Nominal voltage: 10

Material: IEK_V0000193

Min full shrinkage temperature: 150

Operating temperature range: -40...+110

Shrink rate: EV009535

Number of conductors: 3

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/termocontractibil-pkntp-10-3x300-with-pvc-isolation-310647>