

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	IEK TERMOCONTRACTIBIL PKVT-10 1X70/120 WITH PVC ISOLATION Terminations for cables with 10kV cross-linked polyethylene insulation. Heat shrinkable termination couplings for indoor installation are designed for termination of single core aluminium and copper cables with cross-linked polyethylene insulation without armor and with copper wire screen for a voltage of 10kV: APvV-10, APvP-10, APvP2g-10, APvPg-10, APvPu-10, APvPu2g-10, APvPug-10, PvV-10, PvP-10, PvP2g-10, PvPg-10, PvPu-10, PvPu2g-10, PvPug-10, their analogues and modifications. Quick and easy installation of heat-shrinkable coupling components using a gas burner or high-temperature hair dryer. Absolute tightness of the coupling design due to: - application of high-quality two-layer heat-shrinkable materials; - hot-melt adhesive layer on the inner surface of heat-shrinkable tubes and gloves. The set consists of multi-size mechanical lugs with shear bolts and contact paste. Suitable for: EV009729 Model: EV004267 Voltage row: EV004261 Nominal cross section: 70...120 Type of insulation material: IEK V0000184 Installation Type: IEK V0000185 Complete set: IEK V0000188 Number of cores wiring: 1 Tip Type: IEK_V0000189 Nominal voltage: 10 Material: IEK V0000193 Min full shrinkage temperature: 150 Operating temperature range: -40...+110 Shrink rate: EV009535 Number of conductors: 1 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialelectrice.ro/termocontractibil-pkvt-10-1x70-120-with-pvc-isolation-310654
---	---