



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



IEK CONTACTOR KMI-35032 REVERSIBIL 50A 230V/AC3 2NO;2NC

IEK KMI (reverse) contactors are used for starting, stopping and reversing asynchronous electric motors, as well as for remote control of lighting circuits, heating circuits and various low-inductive loads (AC-1 application category). They are supplied with factory tires and mechanical locking. In terms of design and technical characteristics, small-sized contactors of KMI (reverse) IEK comply with the requirements of international and Russian standards GOST R 50030.4.1-2012 (IEC 60947-4-1:2009): they have passed certification tests and received a certificate of compliance with ROSS CN.ME86.B00144 for their serial production. The scope of application of small-sized contactors of the KMI series is the control of fans, pumps, heat curtains, furnaces, crane beams, machine tools, lighting, in automatic reserve input systems (AVR). High electrical and mechanical wear resistance.

A wide range of products.

Compatible with all auxiliary devices for contactors. Rated operation power at AC-3, 400 V: 22.0

Rated control supply voltage Us at DC: -Rated control supply voltage Us at AC 50HZ: 230 Rated operation current Ie at AC-3, 400 V: 50

Degree of protection (IP): EV006405 Voltage type for actuating: EV000460

Connection type main current circuit: EV000415 Function: EV003958 Pret: 0,00 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/contactor-kmi-35032-reversibil-50a-230v-ac3-2no-2nc-311631