

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**IEK PORNIRE MOTOR KMI48062 80A IP54 WITH INDICATION  
UE=230V/AC3**

KMI AC contactors with thermal electrical relay in a protective enclosure represent a complete device consisting of a compact contactor KMI, RTI thermal electrical relay, enclosure with glands and control buttons. Intended for remote actuation by means of direct connection to the network and shutting down three-phase asynchronous electric motors with a short-circuited rotor for the applied voltage limited to 400 V as well as for protecting electric motors from overloads of inadmissible duration and overcurrents arising in case of one phase retardation. Applying KMI 10910 + KMI 23211 contactors predetermines the use of a plastic enclosure; KMI 34012 + KMI 49512 are supplemented with a metal one. Correspond to the requirements of EN 60947-1, EN 60947-4-1, EN 60947-5-1. There is one NO contact group built in the control coil module in the circuit of every contactor. Owing to the push-button control station, this provides for assembling a simple control circuit. Rated control supply voltage  $U_s$  at AC 50Hz: 400  
Rated control supply voltage  $U_s$  at DC: -  
Voltage type for actuating: EV000460  
Rated operation power at AC-3, 400 V: 37  
Rated operation current  $I_e$ : 125  
Conditioned rated short-circuit current  $I_q$ : 5  
Setting range over-current release: 63...80  
Connection type main current circuit: EV000415  
Degree of protection (IP): EV006419

Pret: 808,33 lei (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/contactor-kmi48062-80a-ip54-with-indication-ue-230v-ac3-11662>