



Furnizor: Sc Trivolt Distribution SRL Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



IEK CONTACT EXTENSIONS PKI-04 ADDITIONAL CONTACTS 4P

PKI contact devices are intended for expanding the possibilities of contactor application within technology project automation systems. High speed response. Type of set-up:

Contactor design: Đ'Ñе Ñ,Đ Đ¿Đ¾Đ ,ÑĐ¿Đ¾Đ»Đ½ĐµĐ½Đ ,Ñ ĐšĐœĐ ,ĐšĐ¢Đ Voltage type for actuating: EV000509

Rated operation current Ie at AC-15, 230 V: 6.0
Rated operation current Ie at DC-13, 230 V: 1.5
Rated control supply voltage Us at AC 50HZ: 660/400/230
Rated control supply voltage Us at DC: 400/220
Number of contacts as normally closed contact: 4
Number of contacts as normally contacts of the contact of

Number of contacts as normally open contact: 0

Min on capability at min current: 10.0 Min on capability at min voltage: 24.0 Max short-term load: 100.0

Thermal resistance current: 10.0

Insulation resistance: 10.0

Rated insulation voltage Ui: 690 Max. conductor cross section: 2N...2,5

Max. conductor cross section: 2N...2,5
Mechanical wear resistance: 1,6Ñ...10^6
Degree of protection (IP): EV006405
Operating temperature range: -40...+50
Ambient class: IEK V0000010
Maintainability: EV000494
Nominal operating DC DC-13 400 V: 0.63
Nominal operating current Ie at AC-15 660 V: 1.50
Nominal operating current Ie at AC-15 400 V: 3.00
Width: 440

Width: 44.0 Height: 47.0

Depth: 38.0

Weight: 0.05

Pret: 20,60 lei (TVA inclus)

 $\label{lem:decomposition} \textbf{Detalii online:} \ https://www.materialeelectrice.ro/contact-extensions-pki-04-additional-contacts-4p-311842$