

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **IEK CONTACT EXTENSIONS PKI-11 ADDITIONAL CONTACTS 1Z+1P**

PKI contact devices are intended for expanding the possibilities of contactor application within technology project automation systems. High speed response. Type of set-up: EV003970

Contactor design:  $\bar{D}'\bar{N}\bar{D}\mu\bar{N}, \bar{D}, \bar{D}_z\bar{D}^{3/4}\bar{D}, \bar{N}\bar{D}_z\bar{D}^{3/4}\bar{D} \gg \bar{D}^{1/2}\bar{D}\mu\bar{D}^{1/2}\bar{D}, \bar{N}\bar{D}\bar{D}\bar{D}\bar{D}\bar{D}, \bar{D}\bar{D}\bar{D}\bar{D}\bar{D}$

Voltage type for actuating: EV000509

Rated operation current  $I_e$  at AC-15, 230 V: 6.0

Rated operation current  $I_e$  at DC-13, 230 V: 1.5

Rated control supply voltage  $U_s$  at AC 50HZ: 660/400/230

Rated control supply voltage  $U_s$  at DC: 400/220

Number of contacts as normally closed contact: 1

Number of contacts as normally open contact: 1

Min on capability at min current: 10.0

Min on capability at min voltage: 24.0

Max short-term load: 100.0

Thermal resistance current: 10.0

Insulation resistance: 10.0

Rated insulation voltage  $U_i$ : 690

Max. conductor cross section: 2 $\bar{N}$ ...2,5

Mechanical wear resistance: 1,6 $\bar{N}$ ...10<sup>6</sup>

Degree of protection (IP): EV006405

Operating temperature range: -40...+50

Ambient class: IEK V0000010

Maintainability: EV000494

Nominal operating DC DC-13 400 V: 0.63

Nominal operating current  $I_e$  at AC-15 660 V: 1.50

Nominal operating current  $I_e$  at AC-15 400 V: 3.00

Width: 25.0

Height: 47.0

Depth: 38.0

Weight: 0.03

Pret: 15,17 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/contact-extensions-pki-11-additional-contacts-1z-1p-311843>