

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK JOYSTICK LA167-PA12 2 2 POSITION 2NC NEGRU

The joystick is designed to provide intuitive control of the equipment. Easy installation in standard 22 mm seats provides a variety of applications of the control device in various variations of control and monitoring equipment. High wear resistance.

Fast closing/opening.

Versatility and a wide range. Number of poles: 1

Max. rated operation voltage U_e AC: 400

Rated permanent current I_u : 7.5

Number of switch positions: 2

Device construction: EV002104

Type of control element: IEK_V0000601

Degree of protection (IP), front side: EV006415

Number of auxiliary contacts as normally open contact: 2

Connection type main current circuit: EV000415

Number of auxiliary contacts as normally closed contact: 0

Rated insulation voltage U_i : 660

Nominal heat current I_h : 10

Rated operation current I_e at AC-15, 230 V: 7,5

Nominal operating current I_e at AC-15 400V: 4,5

Electric wear resistance: 0,3

Mechanical wear resistance: 0,6

Degree of Protection - IP Side of Contacts: EV006404

Ambient temperature: -10...+40

Nominal operating voltage AC contacts: 110; 230; 400; 660

Nominal operating voltage DC contacts: 24; 48; 110; 220; 440

Diameter openings: 22.0

Nominal Attachment Capacity: 2Ñ...2,5

Width: 40.0

Height: 30.0

Depth: 148.0

Type of switch: RV001225

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/joystick-la167-pa12-2-2-position-2nc-negru-312067>