



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 ( primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Banca: BRD IBAN: RO34BRDE441SV13182234410

## IEK JOYSTICK LA167-PA14 4 POSTION 4NC NEGRU

The joystick is designed to provide intuitive control of the equipment. Easy installation in<br/>standard 22 mm seats provides a variety of applications of the control device in various<br/>variations of control and monitoring equipment. High wear resistance.<br/>Fast closing/opening.<br/>Versatility and a wide range. Number of poles: 1<br/>Max. rated operation voltage Ue AC: 400<br/>Rated permanent current lu: 7.5<br/>Number of switch positions: 4<br/>Device construction: EV002104<br/>Type of control element: IEK V000601<br/>Degree of protection (IP), front side: EV006415<br/>Number of auxiliary contacts as normally open contact: 4<br/>Connection type main current circuit: EV006415<br/>Number of auxiliary contacts as normally closed contact: 0<br/>Rated insultation voltage U: 660<br/>Nominal heat current The: 10<br/>Rated operating current Ie at AC-15, 230 V: 7,5<br/>Nominal operating current Ie at AC-15 400V: 4,5<br/>Electric wear resistance: 0,6<br/>Degree of Protection - IP Side of Contacts: EV006404<br/>Ambient temperature: -10...440<br/>Nominal operating voltage AC contacts: 24; 48; 110; 220; 440<br/>Diameter openings: 22.0<br/>Nominal duperating voltage AC contacts: 24; 48; 110; 220; 440<br/>Diameter openings: 22.0<br/>Nominal duperating voltage AC contacts: 24; 48; 110; 220; 440<br/>Diameter openings: 22.0<br/>Nominal attachment Capacity: 2Ñ...2,5<br/>Width: 40.0<br/>Height: 30.0<br/>Depth: 148.0<br/>Type of switch: RV001226<br/>Pret: 0,00 lei (TVA inclus)Detalii online: https://www.materialeelectrice.ro/joystick-la167-pa14-4-postion-4nc-<br/>negru-312068