



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



IEK SELECTOR AKS-22 NEGRU WITH KEY 2 FIXED POSITIONS I-O 1C+1R

Control buttons and switches are designed for an operative management of contactors (automatic tripping contactors) and automatics relay within AC electric circuits of 50 Hz and voltage limited to 600 V or DC circuits limited to 400 V and other technological processes. Various color variants provide for the most efficient arrangement of panels and boards. All devices consist of two units: removable head and contact module. Black NO contact block (1NO) and brown NC unit (1NC).Low cost, high reliability and ease of

The wide range allows to complete a case of any complexity. Number of poles: 1

Max. rated operation voltage Ue AC: 660 Rated permanent current Iu: 7.5

Number of switch positions: 2 Device construction: EV002104 Type of control element: EV004094

Degree of protection (IP), front side: EV006415

Number of auxiliary contacts as normally open contact: 1 Connection type main current circuit: EV000415

Connection type main current circuit: EV000415
Number of auxiliary contacts as normally closed contact: 1
Rated insulation voltage Ui: 660
Nominal heat current Th: 10
Rated operation current Ie at AC-15, 230 V: 7,5
Nominal operating current Ie at AC-15 400V: 4,5
Electric wear resistance: 0,3

Degree of Protection - IP Side of Contacts: EV006404
Ambient temperature: -10...+40
Nominal operating voltage AC contacts: 110; 230; 400; 660
Nominal operating voltage DC contacts: 24; 48; 110; 220; 440
Diameter openings: 22.0
Nominal voltage DC: 440

Nominal Attachment Capacity: 2Ñ...2,5 Width: 30.0

Height: 48.0 Depth: 93.0

Type of switch: EV009208 Pret: 27.76 lei (TVA inclus)

 $\label{lem:decomposition} \textbf{Detalii online:} \ https://www.materialeelectrice.ro/selector-aks-22-negru-with-key-2-fixed-positions-i-o-1c-1r-312246$