



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD IBAN: RO34BRDE441SV13182234410



IEK SELECTOR LAY5-BG45 PENTRU 2 POSITIONS WITH KEY

Control buttons and switches are designed for an operative management of contactors (automatic tripping contactors) and automatics relay within AC electric circuits of $50~\rm Hz$ and voltage limited to $600~\rm V$ or DC circuits limited to $400~\rm V$ and other technological processes. Various color variants provide for the most efficient arrangement of panels and boards. All devices consist of two units: removable head and contact module. Black NO contact block (1NO) and brown NC unit (1NC).Low cost, high reliability and ease of installation.

The wide range allows to complete a case of any complexity. Number of poles: 1

Max. rated operation voltage Ue AC: 600 Rated permanent current Iu: 7.5

Number of switch positions: 2 Device construction: EV002104 Type of control element: EV004094

Type of control element: EV004094
Degree of protection (IP), front side: EV006415
Connection type main current circuit: EV000415
Rated insulation voltage Ui: 600
Nominal heat current Th: 10
Rated operation current Ie at AC-15, 230 V: 3,0
Nominal operating current Ie at AC-15 400V: 1,5
Degree of Protection - IP Side of Contacts: EV006405
Ambient temperature: -10...+40
Nominal operating voltage AC contacts: 110; 230; 400; 600
Nominal operating voltage DC contacts: 24; 48; 110; 220; 400
Diameter openings: 22.0
Nominal voltage DC: 400
Nominal Attachment Capacity: 2Ñ...2,5
Width: 39.5

Width: 39.5 Height: 29.5 Depth: 62.0

Type of switch: EV006495 Pret: 32,84 lei (TVA inclus)

 $\begin{tabular}{ll} \textbf{Detalii on line:} & \textbf{https://www.materialeelectrice.ro/selector-lay5-bg45-pentru-2-positions-with-key-312271} \\ \end{tabular}$