

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>IEK ALUMINUM PINI NK 2,0-2,5 5,1 MM (100 PCS.)</u> These terminals are intended for terminating copper wires and are used when mounting electrical distribution units providing for corresponding tie-down on the basis of screw fixation. Devices can be used in vibration environment, as weakening of screw fixation does not lead to losing electrical connection. D̑orrespond to EN 60998-1, EN 60998-2. Dual-profile crimper in the conductor and the insulation provides a special mechanical strength and vibration resistance of connections. Excellent for use at high temperatures. Internal size of connected parts: 5.0 Ambient class: IEK_V0000067 Material insulation: EV008336 Material: EV000138 Bolt dimension metric (M.): - External size of connected parts: 9.0 Nominal voltage: 400 Nominal cross section: 2,0...2,5 Total length: 20.0 Ambient temperature: -40...80 Flange shape: EV003956 Colour insulation: EV008336 Pret: 18,51 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/aluminum-pini-nk-2-0-2-5-5-1-mm-100-pcs-312358
---	--