

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>IEK INSULATED CONNECTING MUFA WITH SOLDER GSI-P 0.5-1.5</u> <u>(100PCS/PACK)</u> Sleeves GSI-p are designed for quick connection of copper or aluminum conductors with a cross section of 0.5 to 1.5 mm² and hermetic insulation of joints. Easy installation. Does not require the use of rosin. The heat resistance of insulation is 105°C. The material of body is heat-shrinkable polyethylene. Transparent insulation for additional control during installation. Section of connected conductor: 0,5...1,2 Model: EV009955 Sleeve form: EV009894 Material: EV009526 Surface protection: EV000899 Insulation: EV003897 Colour insulation: EV000233 Type of connection: EV010120 Max current in long-term mode at Umax I_{max}: 19 Extrusion Force: 30 Ambient class: IEK_V0000067 Length: 40.0 Ambient temperature: -40...+105 Mounting temperature: -20...+50 Nominal cross section: 0,5...1,5 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialelectrice.ro/insulated-connecting-mufa-with-solder-gsi-p-0-5-1-5-100pcs-pack-312398
---	---