

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>IEK INSULATED CONNECTING MUFA WITH SOLDER GSI-P 1.5-2.5</u> <u>(100PCS/PACK)</u> Sleeves GSI-p are designed for quick connection of copper or aluminum conductors with a cross section of 0.5 to 1.5 mm² and hermetic insulation of joints. Easy installation. Does not require the use of rosin. The heat resistance of insulation is 105°C. The material of body is heat-shrinkable polyethylene. Transparent insulation for additional control during installation. Section of connected conductor: 1,5...2,5 Model: EV009955 Sleeve form: EV009894 Material: EV009526 Surface protection: EV000899 Insulation: EV003897 Colour insulation: EV000080 Type of connection: EV010120 Max current in long-term mode at U_{max} I_{max}: 27 Extrusion Force: 40 Ambient class: IEK_V0000067 Length: 40.0 Ambient temperature: -40...+105 Mounting temperature: -20...+50 Nominal cross section: 1,5...2,5 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/insulated-connecting-mufa-with-solder-gsi-p-1-5-2-5-100pcs-pack-312399
---	--