


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;"><b><u>IEK CUPRU TINNED COUPLING MUFA S GML-4</u></b></p> <p>Designed to connect copper and aluminum conductors. They can be used for connections of types copper/copper, copper/aluminum, aluminum/aluminum. The conductors from both sides shall be of same size. The GML sleeves have a limit stop in the center to make fixing easier, which allows avoiding the non-uniform compression of the conductors to be joined. Cross-section of conductors can be easily identified without need to use technical documentation, since it is designated by figure in the sleeve name. For example, GML-10 sleeve is designed for use with conductors of cross-section 10 mm<sup>2</sup>. GML sleeves have a stopper in the center, which helps to avoid uneven compression of the connected conductors.</p> <p>The cross section of the connected conductors is easy to determine without reference to technical documentation: it is indicated by the number in the marking of the sleeve. For example, the GML-10 sleeve is designed for conductors with a cross section of 10 mm<sup>2</sup>. Reduced Al nominal cross section: -</p> <p>Material: EV004251 Voltage row: EV003896 Length: 20.0 Outer diameter: 4.5 Operating temperature range: -60...+50 Application: EV000154 Minimum Axial Breaking Load: 0.24 Inner diameter: 3.2 Pret: 0,42 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/cupru-tinned-coupling-mufa-s-gml-4-312461">https://www.materialelectrice.ro/cupru-tinned-coupling-mufa-s-gml-4-312461</a></p>
---	---