

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK PINI WITH BOLT NA 150-240 10KW

The bolted terminals and sleeves, like compression terminals and sleeves, are designed for termination of conductors. However they can be fixed without use of expensive equipment. A torque wrench is sufficient. Moreover, their unquestionable advantage is a capability to be used for termination and connection of both copper and aluminum conductors. All products have conductivity according to GOST 17441-84. Applicable for copper and aluminum cores.

The angular location of the bolts to secure the strands.

No special tool is required for installation. Ambient temperature: -60...+80

Cross section form: EV010032

Colour insulation: EV000154

Width: 35.4

Height: 35.5

Length: 110.0

Surface protection: EV000899

Number of screws: 2

Max. conductor cross section: 240

Material: IEK_V0000333

Bolt dimension metric (M.): 20Ñ...1,5

Moment of screw head failure during installation of line cabs: 60

Nominal cross section: 150...240

Operating voltage: 10000

Pret: 61,90 lei (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/pini-with-bolt-na-150-240-10kw-312555>