


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p><u>IEK PINI WITH BOLT NB 35-50 1KW</u></p> <p>The bolted terminals and sleeves, like compression terminals and sleeves, are designed for termination of conductors. However they can be fixed without use of expensive equipment. A torque wrench is sufficient. Moreover, their unquestionable advantage is a capability to be used for termination and connection of both copper and aluminum conductors. All products have conductivity according to GOST 17441-84. Applicable for copper and aluminum cores.</p> <p>No special tool is required for installation. Length: 62.0</p> <p>Surface protection: EV000899</p> <p>Number of screws: 1</p> <p>Max. conductor cross section: 50</p> <p>Material: IEK_V0000333</p> <p>Bolt dimension metric (M.): 12Ñ...1,25</p> <p>Moment of screw head failure during installation of line cabs: 20</p> <p>Nominal cross section: 35...50</p> <p>Operating voltage: 1000</p> <p>Ambient temperature: -60...+80</p> <p>Cross section form: EV010032</p> <p>Colour insulation: EV000154</p> <p>Width: 20.0</p> <p>Pret: 24,42 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/pini-with-bolt-nb-35-50-1kw-312558</p>
--	--