

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



#### **IEK PAPUC NBL 120-300-16/2 35KV**

Universal galvanized cable lugs with shear heads. Designed for termination of any type of cable cores up to 35 kV: aluminum and copper, round and sector, solid and stranded. For any type of cable cores: aluminum and copper, round and sector, solid and stranded.

Provides high installation speed.

Each connector and tip is multi-sized.

Operating voltage up to 35kV.

Bolt heads break off when the tightening torque is reached, which is optimal for a quality connection. Weight: 0,31

Length: 106.7

Surface protection: EV001481

Operating voltage: 35000

Ambient temperature: -60...+50

Cross section form: RV000540

Colour insulation: EV000154

Width: 38.0

Number of screws: 2

Number of screws: 2

Max. conductor cross section: 300

Material: IEK\_V0000333

Bolt dimension metric (M.): 22

Moment of screw head failure during installation of line cabs: 40

Nominal cross section: 120...300

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/papuc-nbl-120-300-16-2-35kv-312565>