

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK TINNED CUPRU PIN TERMINAL NVI-N 1,25-3 0,5-1,5MM (100 PCS.)

Using NVI fork-type tips is preferred when it is necessary to introduce operative changes in electrical connections as in this case there is no need for a total dismounting of tie-down. Weakening the screw fixation is enough. Correspond to EN 60998-1, EN 60998-2-2. When installing the lugs of ISL it is not required to perform a complete dismantling of fasteners, the screw fixing should be just loosened.

Lugs are available in three standard colors (red, blue, yellow). Each color corresponds to a specific wire section range. Internal size of connected parts: 3.2

Ambient class: IEK V0000067

Material insulation: EV000154

Material: EV000149

Bolt dimension metric (M.): -

External size of connected parts: 5.8

Nominal voltage: 600

Nominal cross section: 0,5...1,5

Nominal rated current: 19

Total length: 21.0

Ambient temperature: -40...105

Thickness of a contact part: 0.8

Flange shape: EV003886

Colour insulation: EV000233

Pret: 27,11 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tinned-cupru-pin-terminal-nvi-n-1-25-3-0-5-1-5mm-100-pcs-312593>