

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK TINNED CUPRU TERMINAL NKI2-5 1,5-2,5MM (100 PCS.)

NKI insulated ring tips are intended for terminating copper wires and used when mounting electrical distribution units providing for corresponding tie-down on the basis of screw fixation. Correspond to EN 60998-1, EN 60998-2-2. Lugs are available with insulation of three standard colors (red, blue, yellow). Each color corresponds to a specific wire section range. Internal size of connected parts: 5.3

Ambient class: IEK_V0000067

Max diameter of a cable on isolation: 5.0

Material insulation: EV000163

Material: EV000138

Bolt dimension metric (M.): -

External size of connected parts: 8.5

Nominal voltage: 400

Nominal cross section: 1,5...2,5

Nominal rated current: 27

Total length: 21.8

Ambient temperature: -40...80

Thickness of a contact part: 0.8

Flange shape: EV003956

Colour insulation: EV000080

Pret: 24,18 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/tinned-cupru-terminal-nki2-5-1-5-2-5mm-100-pcs-312633>