

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK TINNED CUPRU TERMINAL NKI-N 5.5-4 4-6MM (100 PCS.)

NKI insulated ring tips are intended for terminating copper wires and used when mounting electrical distribution units providing for corresponding tie-down on the basis of screw fixation. Correspond to EN 60998-1, EN 60998-2-2. When installing the lugs of, IRL (Insulated Ring Lug) does not require a complete dismantling of fasteners, you just loosen the screw fixing.

Lugs are available in three standard colors (red, blue, yellow). Each color corresponds to a specific wire section range. Internal size of connected parts: 4.3

Ambient class: IEK_V0000067

Material insulation: EV000154

Material: EV000149

Bolt dimension metric (M.): -

External size of connected parts: 7.2

Nominal voltage: 600

Nominal cross section: 4...6

Nominal rated current: 49

Total length: 22.7

Ambient temperature: -40...105

Thickness of a contact part: 1.0

Flange shape: EV003956

Colour insulation: EV000234

Pret: 59,90 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tinned-cupru-terminal-nki-n-5-5-4-4-6mm-100-pcs-312635>