

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK TINNED CUPRU TERMINAL NKI-N 2-4 1,5-2,5MM (100 PCS.)

NKI insulated ring tips are intended for terminating copper wires and used when mounting electrical distribution units providing for corresponding tie-down on the basis of screw fixation. Correspond to EN 60998-1, EN 60998-2-2. When installing the lugs of, IRL (Insulated Ring Lug) does not require a complete dismantling of fasteners, you just loosen the screw fixing.
Lugs are available in three standard colors (red, blue, yellow). Each color corresponds to a specific wire section range. Internal size of connected parts: 4.3
Ambient class: IEK_V0000067
Material insulation: EV000154
Material: EV000149
Bolt dimension metric (M.): -
External size of connected parts: 6.6
Nominal voltage: 600
Nominal cross section: 1,5...2,5
Nominal rated current: 27
Total length: 19.4
Ambient temperature: -40...105
Thickness of a contact part: 0.8
Flange shape: EV003956
Colour insulation: EV000080
Pret: 30,92 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tinned-cupru-terminal-nki-n-2-4-1-5-2-5mm-100-pcs-312644>