

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>IEK TINNED CUPRU TERMINAL NKI-T 1,25-6 0,5-1,5MM (100 PCS.)</u> NKI insulated ring tips are intended for terminating copper wires and used when mounting electrical distribution units providing for corresponding tie-down on the basis of screw fixation. Correspond to EN 60998-1, EN 60998-2-2. When installing the lugs of, IRL (Insulated Ring Lug) does not require a complete dismantling of fasteners, you just loosen the screw fixing. Lugs are available in three standard colors (red, blue, yellow). Each color corresponds to a specific wire section range. Internal size of connected parts: 6.4 Ambient class: IEK_V0000067 Material insulation: EV000154 Material: EV000149 Bolt dimension metric (M.): - External size of connected parts: 11.6 Nominal voltage: 600 Nominal cross section: 0,5...1,5 Nominal rated current: 19 Total length: 26.8 Ambient temperature: -40...105 Thickness of a contact part: 0.8 Flange shape: EV003956 Colour insulation: EV000233 Pret: 74,02 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/tinned-cupru-terminal-nki-t-1-25-6-0-5-1-5mm-100-pcs-312654
--	---