

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	IEK CLEME SIR ZVI-3 1,0-2,5MM2 (2 PCS/PACK) Applied for screw connection of conductors, protecting wires from damage and excluding possibility of short circuit to the frame of electric unit. Insulation frame is made of white non-flammable polystyrene or transparent polyethylene. Terminal block and screws - latten alloy. Protection of the wire from damage and exclusion of the possibility of a short circuit to the housing of the electrical installation. Retail pack. Connectable conductor cross section solid-core: 1,0...2,5 Connectable conductor cross section multi-wired: 1,0...2,5 Rated current In: 3 Nominal rated voltage: 400 Type of electrical connection 2: EV000415 Connection position: EV001224 Number of poles: 12 Number of clamp positions per pole: 2 Mounting method: EV005276 Material insulation body: EV003904 Operation temperature: -25...+85 Width/grid dimension: 16.0 Length: 92 Colour: EV000202 Rated insulation voltage Ui: 450 Material clamp: EV000149 Material housing: EV000934 Ambient class: IEK_V0000067 Degree of protection (IP): EV006404 Width: 16 Height: 11 Allowable long-term current: 3 Tightening torque Nm at conductor section: 0,8 Max operating voltage Ue: 400 Quantity in the kit: 2 Type of electrical connection 1: EV000415 Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialelectrice.ro/cleme-sir-zvi-3-1-0-2-5mm2-2-pcs-pack-312911
---	--