

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>IEK CLEME SIR ZVI-10 2,5-6MM2 12STEAM NEGRU</u> Applied for screw connection of conductors, protecting wires from damage and excluding possibility of short circuit to the frame of electric unit. Insulation frame is made of white non-flammable polystyrene or transparent polyethylene. Terminal block and screws - latten alloy. Protection of the wire from damage and exclusion of the possibility of a short circuit to the housing of the electrical installation. Fire-retardant housing. Connectable conductor cross section solid-core: 2,5...6 Connectable conductor cross section multi-wired: 2,5...6 Rated current In: 10 Nominal rated voltage: 400 Type of electrical connection 2: EV000415 Connection position: EV001224 Number of poles: 12 Number of clamp positions per pole: 2 Mounting method: EV005276 Material insulation body: EV003904 Operation temperature: -25...+110 Width/grid dimension: 21.0 Length: 128 Colour: EV000206 Rated insulation voltage Ui: 450 Material clamp: EV000149 Material housing: EV003904 Ambient class: IEK_V0000067 Degree of protection (IP): EV006404 Width: 21 Height: 16 Allowable long-term current: 10 Tightening torque Nm at conductor section: 0,8 Max operating voltage Ue: 400 Type of electrical connection 1: EV000415 Pret: 6,33 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/cleme-sir-zvi-10-2-5-6mm2-12steam-negru-312940
---	--