


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;">IEK CLEME DE CAPAT KZVI 4,0MM2 (10X1)</p> <p>IEK screw terminal KZVI is used for screw connection of conductors, protecting the wire from damage and eliminating the possibility of a short circuit to the electrical installation case. CSVI housing is fully protected against short-circuit screw contact groups with each other or the metal housing plug-in electrical products. The screw connection is vibration resistant. The connection of cables and wires with the help of CSVI allows you to securely fix several wires together. Connectable conductor cross section fine-strand without cable end sleeve: 2Ń...4 Connectable conductor cross section solid-core: 2Ń...4 Connectable conductor cross section multi-wired: 2Ń...4 Rated current In: 30 Nominal rated voltage: 450 Type of electrical connection 2: EV000415 Connection position: EV000644 Number of poles: 1 Number of clamp positions per pole: 1 Mounting method: EV005276 Material insulation body: EV000154 Operation temperature: -25...+85 Width/grid dimension: 11.7 Height at lowest possible mounting height: 19 Length: 20 Colour: EV000154 Nominal operating AC voltage Ue: 450 Nominal DC operating voltage Ue: 450 Nominal frequency: 50 Rated insulation voltage Ui: 500 Max. conductor cross section: 2Ń...4 Material clamp: EV000149 Ambient class: IEK_V0000067 Degree of protection (IP): EV0006405 Width: 11,7 Height: 18,5 Nominal Attachment Capacity: 2Ń...1,5...2Ń...4 Allowable long-term current: 30 Tightening torque Nm at conductor section: 0,8 Max operating voltage Ue: 450 Quantity in the kit: 20 Type of electrical connection 1: EV000415 Pret: 6,09 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/cleme-de-capat-kzvi-4-0mm2-10x1-312986</p>
---	--