



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD IBAN: RO34BRDE441SV13182234410

IEK TERMOCONTRACTIBIL TTU 1,5/0,75 TRANSPARENT 1 M

The heat-shrink tubes from thin polyethylene are halogen-free and have fire suppression property. The products have good electrical and mechanical properties and are used as insulating and sealing materials. Being heated after putting in stretched state on various items, they shrink and fit close to an item, assuming its shape. The heat-shrink tubes have the following color options: white, yellow, green/yellow, green, red, blue and black. A wide range of different tube diameters for working with conductors of different

The material of the tubes does not contain halogens and are flame-retardant. Model:

EV009713

Inner diameter before heat-shrink: 2,0 Inner diameter after heat-shrink: 1,0

Colour: EV000184

Nominal cross section: 1,4 Material: EV009539 Shrink rate: EV009534

Wall thickness after shrinking: 0,35

Length: 1

Operation temperature: -55...125 Mounting temperature: -10...50
AC 50 Hz operating voltage: ≤ 660
Tensile strength: ≥ 10,4
Volumetric electrical resistance: ≥ 1x10^14

For dielectric strength up to: ≥ 15 Min shrinkage start temperature: 70 Min full shrinkage temperature: 125 Type: EV004267

Pret: 0,54 lei (TVA inclus)

 $\begin{tabular}{ll} \textbf{Detalii online:} & \textbf{https://www.materialeelectrice.ro/termocontractibil-ttu-1-5-0-75-transparent-1-m-313099 \\ \end{tabular}$