

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



# **SCHNEIDER PRIZA, NEW UNICA, MECANISM, 2P E, 16A, FRENCH, CU OBTURATSAU, IP4X, LUCIOS, NETRATAT, ALB**

Schneider Electric New Unica socket-outlet NU303918E is a mechanism in color white. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. This device respects the French standard. The dielectric strength of this socket-outlet is 2000V. Its rated current is 16A. The fixing mode of this device is clip-in. It is 45 mm in width, 45 mm in height 37 mm in depth. With an embedding depth of 27.4 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. It reaches IK04 protection level, which can help protect against impact. This socket-outlet has screw terminals connection terminals. this cover plate is AENOR, NF certified. As a green premium product, this device is environmentally friendly. This socket-outlet is mercury free New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.Main

Range - New Unica

Product or component type - Socket-outlet

device presentation - Mechanism

device mounting - Flush

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - French

Outlet standard description - Pin earth

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 2 modules

Fixing mode - Clip-in

Colour tint - White (RAL 9003)

Connections - terminals - Screw terminals

Cable cross section - 0.5-4 mm<sup>2</sup> cable(s), 2 - cable stiffness: flexible

0.5-4 mm<sup>2</sup> cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Material - PC: mechanism cover

Surface finish - Glossy

Quantity per set - Set of 1 flow-pack

Standards - IEC 60884-1

UNE 20315-1-1

UNE 20315-1-2

DIN VDE 0620-1

Product certifications - NF

AENOR

Embedding depth - 27.4 mm

Depth - 37 mm

Width - 45 mm

Height - 45 mm

Net weight - 0.031 kg

Surface treatment - Untreated

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5 to 35 A°C

Ambient air temperature for storage - -5 to 50 A°C

IK degree of protection - IK04

IP degree of protection - IP4X

Environmental characteristic - Acetone

Bleach

UV resistant

Petrol

Oil

Alcohol

Window-cleaning fluid  
Liquid soap  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 3.7 cm  
Package 1 Width - 4.5 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 31.0 g  
Unit Type of Package 2 - S04  
Number of Units in Package 2 - 140  
Package 2 Height - 30.0 cm  
Package 2 Width - 40.0 cm  
Package 2 Length - 60.0 cm  
Package 2 Weight - 6.934 kg  
Unit Type of Package 3 - P06  
Number of Units in Package 3 - 560  
Package 3 Height - 77.0 cm  
Package 3 Width - 80.0 cm  
Package 3 Length - 60.0 cm  
Package 3 Weight - 34.58 kg  
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/priza-new-unica-mecanism-2p-e-16a-french-cu-obturatsau-ip4x-lucios-netratat-alb-318770>