

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**SCHNEIDER PRIZA, NEW UNICA, MECANISM, 2P E, 16A, FRENCH,
OBTURATSAU, TERMINAL FARA SURUBURI, IP4X, LUCIOS,
ANTIBACTERIAN, ROSU**

Schneider Electric New Unica socket-outlet NU305203T is a mechanism in color red. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. This device respects the French standard. The dielectric strength of this socket-outlet is 2000V. Its rated current is 16A. The device's fixing mode is clip-in. It is 45 mm in width, 45 mm in height 38.3 mm in depth with an embedding depth of 29 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. Besides, it reaches IK04 protection level, which can help protect against impact. Its connection terminals are screwless terminals. The socket-outlet is made of PC, making it resistant and durable. This socket-outlet is NF certified. As a green premium product, this device is environmentally friendly. It is mercury free. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main Range - New Unica

Product or component type - Socket-outlet

device presentation - Mechanism

device mounting - Flush

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - French

Outlet standard description - Pin earth

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 2 modules

Fixing mode - Clip-in

Colour tint - Red (Pantone 1795C)

Connections - terminals - Screwless terminals

Cable cross section - 0.5-2.5 mm² cable(s), 2 - cable stiffness: flexible

0.5-2.5 mm² cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Material - PC: mechanism cover

Surface finish - Glossy

Quantity per set - Set of 1 without packaging

Standards - IEC 60884-1

NF C 61-314

Product certifications - NF

Embedding depth - 29 mm

Depth - 38.3 mm

Width - 45 mm

Height - 45 mm

Net weight - 0.033 kg

Surface treatment - Antibacterial

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5 to 35 °C

Ambient air temperature for storage - -5 to 50 °C

IK degree of protection - IK04

IP degree of protection - IP4X

Environmental characteristic - Acetone

Bleach

UV resistant

Petrol

Oil

Alcohol

Window-cleaning fluid

Liquid soap

	<p>Packing Units Unit Type of Package 1 - PCE Number of Units in Package 1 - 1 Package 1 Height - 4.0 cm Package 1 Width - 4.5 cm Package 1 Length - 4.5 cm Package 1 Weight - 33.0 g Unit Type of Package 2 - BB1 Number of Units in Package 2 - 10 Package 2 Height - 5.3 cm Package 2 Width - 10.2 cm Package 2 Length - 27.5 cm Package 2 Weight - 401.0 g Unit Type of Package 3 - S01 Number of Units in Package 3 - 20 Package 3 Height - 15.0 cm Package 3 Width - 15.0 cm Package 3 Length - 40.0 cm Package 3 Weight - 1.038 kg Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/priza-new-unica-mecanism-2p-e-16a-french-obturatsau-terminal-fara-suruburi-ip4x-lucios-antibacterian-rosu-318785</p>
--	--