

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**SCHNEIDER PRIZA DUBLA, NEW UNICA, MECANISM, 2P E, 16A,
SCHUKO, CU OBTURATSAU, LUCIOS, NETRATAT, ALB**

Schneider Electric New Unica socket-outlet NU306718A is a mechanism in color white with 2 socket outlets. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. And this device is German standard. The dielectric strength level, the voltage that the material this socket-outlet uses can withstand for a given wall thickness before dielectric breakdown, is 2000V. Its rated current is 16A. The device's fixing mode is clip-in. It is 45 mm in width, It is 90 mm in height, 40.4 mm in depth with an embedding depth of 31.1 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. It reaches IK04 protection level, which can help protect against impact. Its connection terminals are IPT (Isolates Piercing Terminal), screw terminals. The socket-outlet is made of PC, making it resistant and durable. This cover plate is AENOR, EAC certified. This device is qualified as a green premium product, with minimal use of hazardous substances. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Socket-outlet

device presentation - Mechanism

device mounting - Flush

Socket number - 2

Outlet poles configuration - 2P + E

outlet standard - Schuko

Outlet standard description - Side earth

Ground lug position - 45A° ground lug

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 4 modules

Fixing mode - Clip-in

Colour tint - White (RAL 9003)

Connections - terminals - Screw terminals

IPT (Isolates Piercing Terminal)

Cable cross section - 0.6-2.5 mm² cable(s), 2 - cable stiffness: flexible

0.6-2.5 mm² cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Material - PC; mechanism cover

Surface finish - Glossy

Quantity per set - Set of 1 flow-pack

Standards - IEC 60884-1

UNE 20315-1-1

UNE 20315-1-2

DIN VDE 0620-1

Product certifications - EAC

AENOR

Embedding depth - 31.1 mm

Depth - 40.4 mm

Width - 45 mm

Height - 90 mm

Net weight - 0.077 kg

Surface treatment - Untreated

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5-35 A°C

Ambient air temperature for storage - -5-50 A°C

IK degree of protection - IK04

IP degree of protection - IP21D

Environmental characteristic - Acetone

Bleach

	UV resistant Petrol Oil Alcohol Window-cleaning fluid Liquid soap Packing Units Unit Type of Package 1 - PCE Number of Units in Package 1 - 1 Package 1 Height - 4.5 cm Package 1 Width - 4.5 cm Package 1 Length - 9 cm Package 1 Weight - 79 g Unit Type of Package 2 - BB1 Number of Units in Package 2 - 10 Package 2 Height - 8 cm Package 2 Width - 22.5 cm Package 2 Length - 28 cm Package 2 Weight - 936 g Unit Type of Package 3 - S04 Number of Units in Package 3 - 90 Package 3 Height - 30 cm Package 3 Width - 40 cm Package 3 Length - 60 cm Package 3 Weight - 9.153 kg Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialelectrice.ro/priza-dubla-new-unica-mecanism-2p-e-16a-schuko-cu-obturatsau-lucios-netratat-alb-318813
--	--