

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**SCHNEIDER PRIZA DUBLA, NEW UNICA, MECANISM, 2P E, 16A,
FRENCH, OBTURATSAU, TERMINAL FARA SURUBURI, IP3X, VOPSIT,
ANTRACIT**

Schneider Electric New Unica socket-outlet NU306954 is a mechanism in color anthracite with 2 socket outlets. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. And this device is French standard. The dielectric strength, which means the electrical strength of its insulator, is 2000V. Its rated current is 16A. The device's fixing mode is clip-in. It is 45 mm in width, It is 90 mm in height, 39.4 mm in depth with an embedding depth of 30 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. It benefits from an elegant matt finishing, constituting an added-value for your interior design. The IP rating of this device is IP21D which is very high. It reaches IK04 protection level, which can help protect against impact. Its connection terminals are screwless terminals. Being made of PC material, this skin is reliable and resistant. This socket-outlet is NF certified. It is mercury free, as well as heavy metal free, taking care of the environment. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Device application - Power supply

Product or component type - Socket-outlet

device presentation - Mechanism

Socket number - 2

Outlet poles configuration - 2P + E

outlet standard - French

Outlet standard description - Pin earth

Ground lug position - 45A° ground lug

Complementary

Cover type - With shutter

device mounting - Flush

Rated current - 16 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 4 modules

Fixing mode - Clip-in

Colour tint - Anthracite (RAL 7021)

Connections - terminals - Screwless terminals

Cable cross section - 0.5-2.5 mm² cable(s), 2 - cable stiffness: flexible

0.5-2.5 mm² cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Material - PC; mechanism cover

Surface finish - Painted

Quantity per set - Set of 1 without packaging

Standards - IEC 60884-1

NF C 61-314

Product certifications - NF

Embedding depth - 30 mm

Depth - 39.4 mm

Width - 45 mm

Height - 90 mm

Net weight - 0.075 kg

Surface treatment - Painted

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5 to 35 A°C

Ambient air temperature for storage - -5 to 50 A°C

IK degree of protection - IK04

IP degree of protection - IP3x

Environmental characteristic - Acetone

Bleach

UV resistant

Petrol

Oil

Alcohol

	<div>Window-cleaning fluid</div> <div>Liquid soap</div> <div>Packing Units</div> <div>Unit Type of Package 1 - PCE</div> <div>Number of Units in Package 1 - 1</div> <div>Package 1 Height - 9.0 cm</div> <div>Package 1 Width - 4.5 cm</div> <div>Package 1 Length - 4.0 cm</div> <div>Package 1 Weight - 72.0 g</div> <div>Unit Type of Package 2 - BB1</div> <div>Number of Units in Package 2 - 10</div> <div>Package 2 Height - 8.0 cm</div> <div>Package 2 Width - 22.5 cm</div> <div>Package 2 Length - 28.0 cm</div> <div>Package 2 Weight - 861.0 g</div> <div>Unit Type of Package 3 - S04</div> <div>Number of Units in Package 3 - 90</div> <div>Package 3 Height - 30.0 cm</div> <div>Package 3 Width - 40.0 cm</div> <div>Package 3 Length - 60.0 cm</div> <div>Package 3 Weight - 8.509 kg</div> <div>Pret: 0,00 lei (TVA inclus)</div> <div>Detalii online: https://www.materialeelectrice.ro/priza-dubla-new-unica-mecanism-2p-e-16a-french-obturatsau-terminal-fara-suruburi-ip3x-vopsit-antracit-318830</div>
--	---