

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER PRIZA, NEW UNICA, MECANISM CU RAMA FIXARE, 2P E, 16A, SCHUKO LUCIOS, NETRATAT, BEJ

Schneider Electric New Unica socket-outlet NU503644 is a mechanism with zamak fixing frame in color beige. The pole configuration of the outlet is 2P + E. This device respects the German standard. The dielectric strength level, the voltage that the material this socket-outlet uses can withstand for a given wall thickness before dielectric breakdown, is 2000V. Its rated current is 16A. The fixing mode of this device is screws or claws. It is 74.5 mm in width, It is 74.5 mm in height, 40 mm in depth with an embedding depth of 30.5 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP20. It reaches IK04 protection level, which can help protect against impact. Its connection terminals are screw terminals. The socket-outlet is made of Cu.Zn33, Cu.Zn37, PC (polycarbonate) GF10 FR, zamak, making it resistant and durable. This socket-outlet is EAC certified. Being environmentally friendly, this socket-outlet is a green premium product. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Socket-outlet

device presentation - Mechanism with zamak fixing frame

device mounting - Flush

Socket number - 1

Outlet poles configuration - 2P + E

Outlet standard deviation - Schuko

Outlet standard description - Side earth

Rated current - 16 A

Complementary

Device application - Power supply

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 2 modules

Fixing mode - Screws or claws

Colour tint - Beige (RAL 1013)

Connections - terminals - Screw terminals

Cable cross section - 0.5-4 mm² cable(s), 2 - cable stiffness: flexible

0.5-4 mm² cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Material - PC: mechanism cover

PC (polycarbonate) GF10 FR: casing

CuZn37: terminals

CuZn33: earth contact

Zamak: fixing frame

Surface finish - Glossy

Quantity per set - Set of 1 flow-pack

Standards - IEC 60884-1

DIN VDE 0620-1

Product certifications - EAC

Embedding depth - 30.5 mm

Depth - 40 mm

Width - 74.5 mm

Height - 74.5 mm

Net weight - 0.0665 kg

Surface treatment - Untreated

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5 to 35 A°C

Ambient air temperature for storage - -5 to 50 A°C

IK degree of protection - IK04

IP degree of protection - IP20

Environmental characteristic - Acetone

Bleach

UV resistant

Petrol

	<p>Oil Alcohol Window-cleaning fluid Liquid soap Packing Units Unit Type of Package 1 - PCE Number of Units in Package 1 - 1 Package 1 Height - 4.0 cm Package 1 Width - 7.5 cm Package 1 Length - 7.5 cm Package 1 Weight - 67.47 g Unit Type of Package 2 - BB1 Number of Units in Package 2 - 10 Package 2 Height - 8.0 cm Package 2 Width - 20.0 cm Package 2 Length - 22.5 cm Package 2 Weight - 774.0 g Unit Type of Package 3 - S04 Number of Units in Package 3 - 120 Package 3 Height - 30.0 cm Package 3 Width - 40.0 cm Package 3 Length - 60.0 cm Package 3 Weight - 9.937 kg Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/priza-new-unica-mecanism-cu-rama-fixare-2p-e-16a-schuko-lucios-netratat-bej-318850</p>
--	--