

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**SCHNEIDER PRIZA, NEW UNICA, MECANISM CU RAMA FIXARE, 2P E,
16A, SCHUKO, TERMINAL FARA SURUBURI, VOPSIT, ALUMINIU**

Schneider Electric New Unica socket-outlet NU505630 is a mechanism with zamak fixing frame in color aluminium. The pole configuration of the outlet is 2P + E. And this device is German standard. The dielectric strength, which means the electrical strength of its insulator, is 2000V. Its rated current is 16A. Screws or claws this socket-outlet for the fixation. It is 74.5 mm in width, 74.5 mm in height 42 mm in depth with an embedding depth of 32 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is brilliant, gaining extra point for your interior design. The IP rating of this device is IP20. Besides, it reaches IK04 protection level, which can help protect against impact. This socket-outlet has screwless terminals connection terminals. Being made of PC material, this socket-outlet is quite reliable and resistant. This socket-outlet is EAC certified. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main Range - New Unica

Product or component type - Socket-outlet
device presentation - Mechanism with zamak fixing frame
device mounting - Flush

Socket number - 1
Outlet poles configuration - 2P + E
outlet standard - Schuko
Outlet standard description - Side earth
Rated current - 16 A

Complementary
Device application - Power supply
[Ue] rated operational voltage - 250 V
Network type - AC

Network frequency - 50/60 Hz
Number of modules - 2 modules
Fixing mode - Screws or claws

Colour tint - Aluminium
Connections - terminals - Screwless terminals
Cable cross section - 0.5-2.5 mm² cable(s), 2 - cable stiffness: flexible
0.5-2.5 mm² cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Material - PC: mechanism cover

PC (polycarbonate) GF10 FR: casing

Zamak: fixing frame

Surface finish - Painted

Quantity per set - Set of 1 flow-pack

Standards - IEC 60884-1

DIN VDE 0620-1

Product certifications - EAC

Embedding depth - 32 mm

Depth - 42 mm

Width - 74.5 mm

Height - 74.5 mm

Net weight - 0.0645 kg

Surface treatment - Painted

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5 to 35 A°C

Ambient air temperature for storage - -5 to 50 A°C

IK degree of protection - IK04

IP degree of protection - IP20

Environmental characteristic - Acetone

Bleach

UV resistant

Petrol

Oil

Alcohol

Window-cleaning fluid

Liquid soap

Packing Units

Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 4.500 cm
Package 1 Width - 7.500 cm
Package 1 Length - 7.500 cm
Package 1 Weight - 64.000 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 8.500 cm
Package 2 Width - 20.000 cm
Package 2 Length - 22.500 cm
Package 2 Weight - 746.000 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 120
Package 3 Height - 30.000 cm
Package 3 Width - 40.000 cm
Package 3 Length - 60.000 cm
Package 3 Weight - 9.606 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/priza-new-unica-mecanism-cu-rama-fixare-2p-e-16a-schuko-terminal-fara-suruburi-vopsit-aluminiu-318861>