

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER GERMAN PRIZA, NEW UNICA, 2PE, 16A, 2 MODULE, ALB

Schneider Electric New Unica socket-outlet NU203618D is a complete mechanism in color white. The pole configuration of the outlet is 2P + E. This device respects the German standard. The dielectric strength, which means the electrical strength of its insulator, is 2000V. Its rated current is 10/16A. The fixing mode of this device is long claws. It is 85 mm in width, 80 mm in height and 40 mm in depth with an embedding depth of 30 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The IP rating of this device is IP20. It reaches IK01 protection level, which can help protect against impact. Its connection terminals are screw terminals. Being made of ASA + PC, PBT (polybutylene terephthalate) GF30 material, this skin is reliable and resistant. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Device application - Power supply

Product or component type - Socket-outlet

device presentation - Complete mechanism

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - Schuko

Outlet standard description - Side earth

Complementary

device mounting - Flush

Rated current - 16 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 2 modules

Fixing mode - Long claws

Colour tint - White (RAL 9003)

Connections - terminals - Screw terminals

Cable cross section - 0.5-4 mm² cable(s), 2 - cable stiffness: flexible

0.5-4 mm² - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Material - PC: mechanism cover

PBT (polybutylene terephthalate) GF30: fixing frame

ABS (acrylonitrile butadiene-styrene): cover frame

Surface finish - Glossy

Quantity per set - Set of 1 flow-pack

Standards - IEC 60884-1

DIN VDE 0620-1

Product certifications - VDE

Embedding depth - 30.5 mm

Depth - 40 mm

Width - 85 mm

Height - 85 mm

Net weight - 0.0391 kg

Surface treatment - Untreated

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5 to 35 °C

Ambient air temperature for storage - -5 to 50 °C

IK degree of protection - IK01

IP degree of protection - IP20

Environmental characteristic - Acetone

Oil

Window-cleaning fluid

Liquid soap

UV resistant

Petrol

Alcohol

Bleach

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 4.5 cm
Package 1 Width - 8.5 cm
Package 1 Length - 8.5 cm
Package 1 Weight - 59 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 10.5 cm
Package 2 Width - 13.5 cm
Package 2 Length - 37 cm
Package 2 Weight - 823 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 80
Package 3 Height - 30 cm
Package 3 Width - 40 cm
Package 3 Length - 60 cm
Package 3 Weight - 7.227 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/german-priza-new-unica-2pe-16a-2-module-alb-318877>