

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER PRIZA DUBLA, NEW UNICA, 2PE, 16A CZ SK, ALB

Schneider Electric New Unica socket-outlet NU206518 is a complete mechanism in color white with 2 socket outlets. The pole configuration of the outlet is 2P + E. And this device is Czech republic, Slovakia standard. The dielectric strength of this socket-outlet is 2000V. Its rated current is 16A.. 2 pins this socket-outlet for the fixation. It is 90.21 mm in width, It is 122.9 mm in height, 37 mm in depth with an embedding depth of 27 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The IP rating of this device is IP20. It reaches IK01 protection level, which can help protect against impact. Its connection terminals are screw terminals. The socket-outlet is made of ABS (acrylonitrile butadiene-styrene), ASA + PC, making it resistant and durable. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Device application - Power supply

Product or component type - Socket-outlet

device presentation - Complete mechanism

Socket number - 2

Outlet poles configuration - 2P + E

outlet standard - Czech Republic

Czech Republic

Socket additional information - Pin earth

Outlet standard description - Pin earth

Complementary

device mounting - Flush

Rated current - 16 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Fixing mode - 2 fixing points

Colour tint - White (RAL 9003)

Connections - terminals - Screw terminals

Cable cross section - 0.5-4 mm² cable(s), 2 - cable stiffness: flexible

0.5-4 mm² - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Material - ASA + PC: mechanism cover

ABS (acrylonitrile butadiene-styrene): cover frame

Surface finish - Glossy

Quantity per set - Set of 1 flow-pack

Standards - IEC 60884-1

Embedding depth - 27 mm

Depth - 35.3 mm

Width - 85 mm

Height - 125 mm

Net weight - 0.0864 kg

Surface treatment - Untreated

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5 to 35 A°C

Ambient air temperature for storage - -5 to 50 A°C

IK degree of protection - IK01

IP degree of protection - IP21D

Environmental characteristic - Alcohol

Bleach

Liquid soap

Acetone

Window-cleaning fluid

UV resistant

Petrol

Oil

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 3.8 cm

Package 1 Width - 8.4 cm

Package 1 Length - 12.5 cm
Package 1 Weight - 86.4 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 5
Package 2 Height - 13.7 cm
Package 2 Width - 10.3 cm
Package 2 Length - 19.3 cm
Package 2 Weight - 488 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 90
Package 3 Height - 30 cm
Package 3 Width - 40 cm
Package 3 Length - 60 cm
Package 3 Weight - 9.487 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/priza-dubla-new-unica-2pe-16a-cz-sk-alb-318881>