

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER AMERICAN PRIZA DUBLA, NEW UNICA, OBTURATSAUOSU, 15 A, 3 MODULE, ALUMINIU

Schneider Electric New Unica socket-outlet NU306030 is a mechanism in color aluminium with 2 socket outlets. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. And this device is American standard. The dielectric strength, which means the electrical strength of its insulator, is 2000V. Its rated current is 15A,16A. The fixing mode of this device is clip-in. It is 45 mm in width, It is 45 mm in height, 33 mm in depth with an embedding depth of 24 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The IP rating of this device is IP20. Besides, it reaches IK01 protection level, which can help protect against impact. Its connection terminals are screw terminals. The socket-outlet is made of ASA + PC, making it resistant and durable. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers

requirements. Main

Range - New Unica

Device application - Power supply

Product or component type - Socket-outlet

device presentation - Mechanism

Socket number - 2

Outlet poles configuration - 2P + E

outlet standard - American

Outlet standard description - Centred earth

Complementary

Cover type - With shutter

device mounting - Flush

Rated current - 15 A

[Ue] rated operational voltage - 127 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 3 modules

Fixing mode - Clip-in

Colour tint - Aluminium

Connections - terminals - Screw terminals

Cable cross section - 0.5-4 mm² - cable stiffness: flexible

0.5-4 mm² - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Material - PC; mechanism cover

PC (polycarbonate) GF10 FR: casing

Surface finish - Painted

Quantity per set - Set of 1 flow-pack

Standards - IEC 60884-1

Embedding depth - 24 mm

Depth - 30 mm

Width - 67.5 mm

Height - 45 mm

Net weight - 0.036 kg

Surface treatment - Painted

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5 to 35 A°C

Ambient air temperature for storage - -5 to 50 A°C

IK degree of protection - IK01

IP degree of protection - IP20

Environmental characteristic - UV resistant

Alcohol

Acetone

Bleach

Liquid soap

Window-cleaning fluid

Petrol

Oil

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 2.95 cm
Package 1 Width - 4.5 cm
Package 1 Length - 6.75 cm
Package 1 Weight - 36 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 5
Package 2 Height - 6.5 cm
Package 2 Width - 12 cm
Package 2 Length - 18.5 cm
Package 2 Weight - 248.3 g
Unit Type of Package 3 - S01
Number of Units in Package 3 - 20
Package 3 Height - 15 cm
Package 3 Width - 15 cm
Package 3 Length - 40 cm
Package 3 Weight - 1.193 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/american-priza-dubla-new-unica-obturatsauosu-15-a-3-module-aluminiu-318922>