

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER CONNECTED SINGLE PRIZA, NEW UNICA, 16 A, SCHUKO, BEJ**

This Schneider Electric Wiser New Unica connected socket outlet is with the ensuring safety protection earthing pin. The outlet pole configuration of this socket-outlet is 2P+E with shutters. The device respects the German (side earth) Outlet standard. This product is compatible with Amazon Alexa (EF014927), Apple HomeKit (EF014925), Google Assistant (EF014926). The device is with 2 modules and fixed with 4 fixing points. The fixing frame of the device is Zamak. Easy installation, screwdriver is not required to connect the cables, thanks to the screwless connection. The operating voltage is 220-240VAC at 50/60Hz and the rated current is 16A. Its has dielectric strength of 2000V. The Socket Outlet is compatible with 3680W Resistive load, 16A Inductive load, and 6AX Capacitive load. The rated Insulation voltage is 500V with an insulation resistance of greater than 5MOhm. This device enables flush mounting. The dimensions are (W) 74.5mm x (H) 74.5mm x (D) 40mm with embedding depth 30.5mm. The weight is 73.9g. The color of this device is Beige with a glossy finish and is made of polycarbonate. The operating temperature is from -5A°C up to +35A°C and the storage temperature is from -5A°C up to +50A°C. It reaches IK05 and IP20 degrees of protection. This product comes in a set of 1 Box carton packaging. Delivered in set of 1 Box packaging. To be completed with the cover frame. The device is fixed with 4 fixing points. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Users benefit from beautiful design that match their style and innovative products. New Unica features innovative functions to carry the range into the smart homes of the future. This device is compliant with the standards of IEC 60884-1, UNE 20315-1-1, and UNE 20315-1-2 and with EAC certifications. Main Range - New Unica

Device application - Power supply

Product or component type - Connected socket-outlet

device presentation - Mechanism with fixing frame

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - Schuko

Outlet standard description - Side earth

Complementary

Cover type - With shutter

device mounting - Flush

Rated current - 16 A

[Ue] rated operational voltage - 220...240 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 2 modules

Fixing mode - 4 fixing points

Colour tint - Beige (RAL 1013)

Connections - terminals - Screwless terminals

Cable cross section - 0.5-2.5 mm<sup>2</sup> cable(s), 2 - cable stiffness: flexible

0.5-2.5 mm<sup>2</sup> cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Material - PC: mechanism cover

Zamak: fixing frame

PC (polycarbonate) GF10 FR: casing

Surface finish - Glossy

Quantity per set - Set of 1 box

Standards - IEC 60884-1

UNE 20315-1-1

UNE 20315-1-2

Product certifications - EAC

Embedding depth - 30.5 mm

Depth - 40 mm

Width - 74.5 mm

Height - 74.5 mm

Net weight - 0.0739 kg

Surface treatment - Untreated

Type of packing - Carton

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5A°C-35 A°C

Ambient air temperature for storage - -5A°C-50 A°C

IK degree of protection - IK05  
IP degree of protection - IP20  
Environmental characteristic - Acetone  
UV resistant  
Petrol  
Oil  
Window-cleaning fluid  
Liquid soap  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 7.7 cm  
Package 1 Width - 9.5 cm  
Package 1 Length - 9.5 cm  
Package 1 Weight - 170.0 g  
Unit Type of Package 2 - S03  
Number of Units in Package 2 - 36  
Package 2 Height - 30.0 cm  
Package 2 Width - 30.0 cm  
Package 2 Length - 40.0 cm  
Package 2 Weight - 6.575 kg  
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/connected-single-priza-new-unica-16-a-schuko-bej-318936>