

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER INTRERUPATOR, NEW UNICA, INTERMEDIATE, 10AX, 2 MODULE, TERMINAL FARA SURUBURI, VOPSIT, IP4X, ALUMINIU

Schneider Electric New Unica switch NU520530 is a mechanism with zamak fixing frame in color aluminium. This is an intermediate switch. The fixing mode of this device is screws or claws. Its rated current is 10AX. It is 74.5 mm in width, It is 74.5 mm in height, 37.75 mm in depth with an embedding depth of 24.65 mm. The surface finish is painted powder coated. The IP rating of this device is IP21D which is very high. This switch has screwless terminals connection terminals. The switch is made of Cu.Zn15, Cu.Zn5 Ag, PBT (polybutylene terephthalate) GF31, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilized, zamak, making it as resistant as possible. It obtained AENOR, CE, EAC, NF certificate. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Switch
device presentation - Mechanism with fixing frame

Technology type - Electromechanical

Switch function - Intermediate

Number of rocker - 1

Device application - Light control

Provided equipment - Fixing frame

Colour tint - Aluminium

Type of packing - Flow-pack

Complementary

Rated current - 10 AX

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Electrical durability - 20000 cycles, cos phi = 0.6

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3

Opening distance - > 3 mm

Actuator - Rocker

Number of modules - 2 modules

Connections - terminals - Screwless terminals

Cable cross section - 0.5-2.5 mm² rigid cable

0.5-2.5 mm² flexible cable

Material - CuZn5 Ag: fixed terminals

CuZn15: mobile contact

PBT (polybutylene terephthalate) GF31: release button

Zamak: fixing frame

Thermoplastic ABS-UV stabilised: mechanism rocker

PC (polycarbonate) GF10 FR: casing

Marking - Without marking

Surface finish - Glossy

specific treatment - integrated within the material - Painted

Fixing mode - Screws or claws

Width - 74.5 mm

Height - 74.5 mm

Depth - 37.75 mm

Embedding depth - 24.65 mm

Net weight - 0.0571 kg

Ambient air temperature for operation - -5 to 40 A°C

Ambient air temperature for storage - -5 to 50 A°C

Standards - LV directive

IEC 60669-1

Product certifications - CE

AENOR

EAC

NF

VDE

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IP degree of protection - IP4X

IK degree of protection - IK04

Environmental characteristic - Oil

UV resistant

	<p>Acetone</p> <p>Liquid soap</p> <p>Window-cleaning fluid</p> <p>Petrol</p> <p>Alcohol</p> <p>Bleach</p> <p>Packing Units</p> <p>Unit Type of Package 1 - PCE</p> <p>Number of Units in Package 1 - 1</p> <p>Package 1 Height - 7.5 cm</p> <p>Package 1 Width - 7.5 cm</p> <p>Package 1 Length - 3.8 cm</p> <p>Package 1 Weight - 56 g</p> <p>Unit Type of Package 2 - CAR</p> <p>Number of Units in Package 2 - 10</p> <p>Package 2 Height - 8.2 cm</p> <p>Package 2 Width - 19.7 cm</p> <p>Package 2 Length - 22.6 cm</p> <p>Package 2 Weight - 665 g</p> <p>Unit Type of Package 3 - S03</p> <p>Number of Units in Package 3 - 50</p> <p>Package 3 Height - 30 cm</p> <p>Package 3 Width - 30 cm</p> <p>Package 3 Length - 40 cm</p> <p>Package 3 Weight - 3763 g</p> <p>Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/intrerupator-new-unica-intermediate-10ax-2-module-terminal-fara-suruburi-vopsit-ip4x-aluminiu-319036</p>
--	---