

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**SCHNEIDER BUTON DUBLU, NEW UNICA, INTERMEDIATE, 10AX, 2
MODULE, TERMINAL FARA SURUBURI, VOPSIT, IP4X, ANTRACIT**

Schneider Electric New Unica switch NU521554 is a mechanism with zamak fixing frame in color anthracite with 2 rockers. This is an intermediate switch. Screws or claws this rocker switch for the fixation. Its rated current is 10AX. It is 74.5 mm in width, 74.5 mm in height and 37.75 mm in depth with an embedding depth of 24.65 mm. The surface finish is painted powder coated. The IP rating of this device is IP21D which is very high. Its connection terminals are screwless terminals. It obtained AENOR, CE, EAC, NF certificate. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica
Product or component type - Switch
device presentation - Mechanism with fixing frame
Technology type - Electromechanical
Switch function - Intermediate
Number of rocker - 2
Device application - Light control
Provided equipment - Fixing frame
Colour tint - Anthracite (RAL 7021)
Type of packing - Flow-pack
Complementary
Rated current - 10 AX
[Ue] rated operational voltage - 250 V
Network type - AC
Network frequency - 50/60 Hz
Electrical durability - 20000 cycles, $\cos \phi = 0.6$
Insulation resistance - $> 5 \text{ MOhm}$ at 500 V
Dielectric strength - 2000 V
Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, $\cos \phi = 0.3$
Opening distance - $> 3 \text{ mm}$
Actuator - Rocker
Number of modules - 2 modules
Connections - terminals - Screwless terminals
Cable cross section - 0.5 mm^2 rigid cable
 0.5 mm^2 flexible cable
Material - CuZn5 Ag: fixed terminals
CuZn15: mobile contact
PBT (polybutylene terephthalate) GF31: release button
Zamak: fixing frame
Thermoplastic ABS-UV stabilised: mechanism rocker
PC (polycarbonate) GF10 FR: casing
Marking - Without marking
Surface finish - Matt
specific treatment - integrated within the material - Painted
Fixing mode - Screws or claws
Width - 74.5 mm
Height - 74.5 mm
Depth - 37.75 mm
Embedding depth - 24.65 mm
Net weight - 0.0763 kg
Ambient air temperature for operation - $-5 \text{ }^\circ\text{C}$ to $40 \text{ }^\circ\text{C}$
Ambient air temperature for storage - $-5 \text{ }^\circ\text{C}$ to $50 \text{ }^\circ\text{C}$
Standards - IEC 60669-1
LV directive
Product certifications - CE
AENOR
EAC
NF
VDE
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
IP degree of protection - IP4X
IK degree of protection - IK04
Environmental characteristic - Oil
UV resistant
Acetone
Liquid soap

Window-cleaning fluid
Petrol
Alcohol
Bleach
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 7.5 cm
Package 1 Width - 7.5 cm
Package 1 Length - 3.8 cm
Package 1 Weight - 75 g
Unit Type of Package 2 - S02
Number of Units in Package 2 - 10
Package 2 Height - 15 cm
Package 2 Width - 30 cm
Package 2 Length - 40 cm
Package 2 Weight - 1174 g
Unit Type of Package 3 - P06
Number of Units in Package 3 - 160
Package 3 Height - 77 cm
Package 3 Width - 80 cm
Package 3 Length - 60 cm
Package 3 Weight - 27284 g
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/buton-dublu-new-unica-intermediate-10ax-2-module-terminal-fara-suruburi-vopsit-ip4x-antracit-319059>