


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER 3 OBTURATSAU CONTROL, NEW UNICA, 3 POSITIONS, 6A, 2 MODULE, TERMINAL FARA SURUBURI, IP4X, ALB**

Schneider Electric New Unica roller blind switch NU520818D is a mechanism with fixing frame in color white. Its connection terminals are screwless terminals. The device's fixing mode is screws or claws. It is 74.5 mm in width, 74.5 mm in height, 44.35 mm in depth, with an embedding depth of 32.8 mm, and the product weighs 0.069 kg. With 2 modules. It is with pilot light without LED. It comes in 3 positions roller blind switch. This product is sold in 10. It obtained AENOR, CE, EAC, NF certificate as well. Being made of Cu. Zn15, PBT (polybutylene terephthalate) GF30, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilised, zamak material, this roller blind switch is quite reliable and resistant. Besides, it reaches IK04 protection level, which can help protect against impact. What's more, it well satisfied the standard of IEC 60669-1, LV directive, Ro. HS compliant. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. The dielectric strength, a measure of the electrical strength of a material as an insulator, is 2000 V. And its rated current is 6A. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Shutter control  
device presentation - Mechanism with fixing frame

Technology type - Electromechanical

Switch function - 3 positions

Number of rocker - 3

Device application - Control

Provided equipment - Fixing frame

Colour tint - White (RAL 9003)

Type of packing - Flow-pack

Complementary

Rated current - 6 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Electrical durability - 20000 cycles, cos phi = 0.6

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3

Opening distance - > 3 mm

Actuator - Rocker and push-button

Number of modules - 2 modules

Connections - terminals - Screwless terminals

Cable cross section - 0.5-2.5 mm<sup>2</sup> rigid cable

0.5-2.5 mm<sup>2</sup> flexible cable

Material - CuZn15: terminals

Zamak: fixing frame

Thermoplastic ABS-UV stabilised: mechanism rocker

PC (polycarbonate) GF10 FR: casing

PBT (polybutylene terephthalate) GF30: release button

Marking - 0 position

Arrow

Surface finish - Glossy

Fixing mode - Screws or claws

Width - 74.5 mm

Height - 74.5 mm

Depth - 44.35 mm

Embedding depth - 32.8 mm

Net weight - 0.069 kg

Ambient air temperature for operation - -5 to +40 A°C

Ambient air temperature for storage - -5 to +50 A°C

Standards - LV directive

IEC 60669-1

Product certifications - CE

AENOR

EAC

NF

VDE

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IP degree of protection - IP4X  
IK degree of protection - IK04  
Environmental characteristic - Oil  
UV resistant  
Acetone  
Liquid soap  
Window-cleaning fluid  
Petrol  
Alcohol  
Bleach  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 4.5 cm  
Package 1 Width - 7.5 cm  
Package 1 Length - 7.5 cm  
Package 1 Weight - 68 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 5  
Package 2 Height - 10.3 cm  
Package 2 Width - 13.7 cm  
Package 2 Length - 19.3 cm  
Package 2 Weight - 396 g  
Unit Type of Package 3 - S04  
Number of Units in Package 3 - 90  
Package 3 Height - 30 cm  
Package 3 Width - 40 cm  
Package 3 Length - 60 cm  
Package 3 Weight - 7.831 kg  
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/3-obturatsau-control-new-unica-3-positions-6a-2-module-terminal-fara-suruburi-ip4x-alb-319080>