

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER CAP SCARA, NEW UNICA, 10 A, CU STUDIO FRAME, ALUMINIU**

Schneider Electric New Unica switch NU220330D is a complete mechanism in color aluminium and cream. This is a 1-pole 2-way switch that comes with a studio frame. The fixing mode of this device is long claws. Its rated current is 10A. It is 85 mm in width, 80 mm in height 34 mm in depth with an embedding depth of 22 mm. The IP rating of this device is IP20. This switch has screwless terminals connection terminals. Being made of ABS (acrylonitrile butadiene-styrene) material, this skin is reliable and resistant. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Switch

device presentation - Complete product

Technology type - Electromechanical

Switch function - 1-pole 2-way

Number of rocker - 1

Device application - Light control

Colour tint - Aluminium

Cream

Type of packing - Flow-pack

Complementary

Rated current - 10 A

10 AX

[Ue] rated operational voltage - 250 V

250 V

Network type - AC

AC

Network frequency - 50/60 Hz

50/60 Hz

Electrical durability - 10000 cycles

20000 cycles, cos phi = 0.6

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3

Condition of use - Indoor

Opening distance - > 3 mm

Actuator - Rocker

Number of modules - 2 modules

Connections - terminals - Screwless terminals

Cable cross section - 0.5-2.5 mm<sup>2</sup> rigid cable

0.5-2.5 mm<sup>2</sup> flexible cable

Material - ABS (acrylonitrile butadiene-styrene): mechanism cover

ABS (acrylonitrile butadiene-styrene): cover frame

Surface finish - Glossy

specific treatment - integrated within the material - Painted

Fixing mode - Long claws

Width - 85 mm

Height - 85 mm

Depth - 34.25 mm

Embedding depth - 21.15 mm

Net weight - 0.057 kg

Ambient air temperature for operation - -5 to +40 A°C

Ambient air temperature for storage - -5 to +50 A°C

Standards - EN 60669-1

LV directive

EMC directive

Product certifications - CE

AENOR

EAC

NF

VDE

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IP degree of protection - IP4X

IK degree of protection - IK04

Environmental characteristic - Acetone

Alcohol

	<p>Liquid soap Petrol UV resistant Bleach Oil Window-cleaning fluid Packing Units Unit Type of Package 1 - PCE Number of Units in Package 1 - 1 Package 1 Height - 5 cm Package 1 Width - 8.5 cm Package 1 Length - 8.5 cm Package 1 Weight - 68 g Unit Type of Package 2 - BB1 Number of Units in Package 2 - 10 Package 2 Height - 12 cm Package 2 Width - 17.5 cm Package 2 Length - 26 cm Package 2 Weight - 815 g Unit Type of Package 3 - S04 Number of Units in Package 3 - 80 Package 3 Height - 30 cm Package 3 Width - 40 cm Package 3 Length - 60 cm Package 3 Weight - 7.223 kg Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialeelectrice.ro/cap-scara-new-unica-10-a-cu-studio-frame-aluminiu-319091">https://www.materialeelectrice.ro/cap-scara-new-unica-10-a-cu-studio-frame-aluminiu-319091</a></p>
--	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------