


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER INTRERUPATOR, NEW UNICA, 10 A, 1 MODULE, BEI

Schneider Electric New Unica switch NU310144SC is a mechanism in color beige. This is a 1-pole 1-way switch. The device's fixing mode is clip-in. Its rated current is 10A. It is 22.5 mm in width, 45 mm in height 33.8 mm in depth with an embedding depth of 21.7 mm. It reaches IP20 degree of protection which is very high. Its connection terminals are screw terminals. The switch is made of ASA + PC, making it resistant and durable. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Switch

device presentation - Mechanism

Technology type - Electromechanical

Switch function - 1-pole 1-way

Number of rocker - 1

Device application - Light control

Colour tint - Beige (RAL 1013)

Type of packing - Flow-pack

Complementary

Rated current - 10 A

10 AX

[Ue] rated operational voltage - 250 V

250 V

Network type - AC

AC

Network frequency - 50/60 Hz

50/60 Hz

Electrical durability - 10000 cycles

20000 cycles, cos phi = 0.6

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3

Condition of use - Indoor

Opening distance - > 3 mm

Actuator - Rocker

Number of modules - 1 module

Connections - terminals - Screw terminals

Cable cross section - 0.5-2.5 mm² rigid cable

0.5-2.5 mm² flexible cable

Material - ASA + PC: mechanism cover

ABS (acrylonitrile butadiene-styrene): mechanism cover

Surface finish - Glossy

specific treatment - integrated within the material - Untreated

Fixing mode - Clip-in

Width - 22.5 mm

Height - 45 mm

Depth - 34.25 mm

Embedding depth - 21.15 mm

Net weight - 0.019 kg

Ambient air temperature for operation - -5 to 40 A°C

Ambient air temperature for storage - -5 to 50 A°C

Standards - EN 60669-1

LV directive

EMC directive

Product certifications - CE

AENOR

EAC

NF

VDE

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IP degree of protection - IP4X

IK degree of protection - IK04

Environmental characteristic - Oil

UV resistant

Acetone

Liquid soap

Window-cleaning fluid

Petrol
Alcohol
Bleach
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 3.5 cm
Package 1 Width - 2.25 cm
Package 1 Length - 4.5 cm
Package 1 Weight - 16 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 20
Package 2 Height - 8.2 cm
Package 2 Width - 17.7 cm
Package 2 Length - 18.5 cm
Package 2 Weight - 404 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 400
Package 3 Height - 30 cm
Package 3 Width - 40 cm
Package 3 Length - 60 cm
Package 3 Weight - 8.783 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/intrerupator-new-unica-10-a-1-module-bej-319101>