

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER INTREERUPATOR, NEW UNICA, 10 A, LED, ALB**

Schneider Electric New Unica switch NU520118NZ is a mechanism with zamak fixing frame + long claws in color white. This is a 1-pole 1-way switch. Long claws this rocker switch for the fixation. Its rated current is 10A. It is 70.9 mm in width, It is 70.9 mm in height, 34 mm in depth with an embedding depth of 22 mm. The IP rating of this device is IP20. This switch has screwless terminals connection terminals. Zamak Besides, there is a RIGHT marking on the surface. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Switch

device presentation - Mechanism with fixing frame

Technology type - Electromechanical

Switch function - 1-pole 1-way

Number of rocker - 1

Device application - Light control

Colour tint - White (RAL 9003)

Type of packing - Flow-pack

Complementary

Rated current - 10 A

10 AX

[Ue] rated operational voltage - 250 V

250 V

Network type - AC

AC

Network frequency - 50/60 Hz

50/60 Hz

Electrical durability - 10000 cycles

20000 cycles, cos phi = 0.6

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3

Condition of use - Indoor

Opening distance - > 3 mm

Actuator - Rocker

Number of modules - 2 modules

Pilot light - LED, colour: blue, current consumption: 0.15 mA, temperature rise: 15 A°C

LED, colour: white, current consumption: 0.05 mA, temperature rise: 15 A°C

Connections - terminals - Screwless terminals

Cable cross section - 0.5-2.5 mmA<sup>2</sup> rigid cable

0.5-2.5 mmA<sup>2</sup> flexible cable

Material - Zamak: fixing frame

Marking - RIGHT

Surface finish - Glossy

specific treatment - integrated within the material - Untreated

Fixing mode - Long claws

Width - 70.9 mm

Height - 70.9 mm

Depth - 34 mm

Embedding depth - 22 mm

Net weight - 0.0616 kg

Ambient air temperature for operation - -5A°C-40 A°C

Ambient air temperature for storage - -5A°C-50 A°C

Standards - EN 60669-1

LV directive

EMC directive

Product certifications - CE

AENOR

EAC

NF

VDE

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IP degree of protection - IP4X

IK degree of protection - IK04

Environmental characteristic - Liquid soap

Petrol

Bleach

UV resistant  
Oil  
Window-cleaning fluid  
Acetone  
Alcohol  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 5 cm  
Package 1 Width - 7.5 cm  
Package 1 Length - 7.5 cm  
Package 1 Weight - 64 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 10  
Package 2 Height - 8.2 cm  
Package 2 Width - 19.7 cm  
Package 2 Length - 22.6 cm  
Package 2 Weight - 745 g  
Unit Type of Package 3 - S03  
Number of Units in Package 3 - 50  
Package 3 Height - 30 cm  
Package 3 Width - 30 cm  
Package 3 Length - 40 cm  
Package 3 Weight - 4.166 kg  
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-new-unica-10-a-led-alb-319127>