

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER INTRERUPATOR CAP CRUCE, NEW UNICA, 10 A, ALB

Schneider Electric New Unica switch NU520518Z is a mechanism with zamak fixing frame + long claws in color white. This is an intermediate switch. Long claws this rocker switch for the fixation. Its rated current is 10A. It is 70.9 mm in width, 70.9 mm in height and 34 mm in depth with an embedding depth of 22 mm. It reaches IP20 degree of protection which is very high. This switch has screwless terminals connection terminals. The switch is made of zamak, making it as resistant as possible. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.

Main

Range of product - New Unica

Product or component type - Switch

device presentation - Mechanism with fixing frame

Technology type - Electromechanical

Switch function - Intermediate

Number of rocker - 1

Device application - Light control

Colour tint - White (RAL 9003)

Type of packing - Flow-pack

Complementary

Rated current - 10 A

10 AX

[Ue] rated operational voltage - 250 V

250 V

Network type - AC

AC

Network frequency - 50/60 Hz

50/60 Hz

Electrical durability - 10000 cycles

20000 cycles, cos phi = 0.6

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3

Condition of use - Indoor

Opening distance - > 3 mm

Actuator - Rocker

Number of modules - 2 modules

Connections - terminals - Screwless terminals

Cable cross section - 0.5-2.5 mm² rigid cable

0.5-2.5 mm² flexible cable

Material - Zamak: fixing frame

Surface finish - Glossy

specific treatment - integrated within the material - Untreated

Fixing mode - Long claws

Width - 70.9 mm

Height - 70.9 mm

Depth - 34 mm

Embedding depth - 22 mm

Net weight - 0.0647 kg

Ambient air temperature for operation - -5 to +40 A°C

Ambient air temperature for storage - -5 to +50 A°C

Standards - EN 60669-1

LV directive

EMC directive

Product certifications - CE

AENOR

EAC

NF

VDE

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IP degree of protection - IP4X

IK degree of protection - IK04

Environmental characteristic - Bleach

Oil

UV resistant

Liquid soap

Acetone

	<div>Petrol Alcohol Window-cleaning fluid Packing Units Unit Type of Package 1 - PCE Number of Units in Package 1 - 1 Package 1 Height - 5 cm Package 1 Width - 7.5 cm Package 1 Length - 7.5 cm Package 1 Weight - 64 g Unit Type of Package 2 - BB1 Number of Units in Package 2 - 10 Package 2 Height - 8.2 cm Package 2 Width - 19.7 cm Package 2 Length - 22.6 cm Package 2 Weight - 745 g Unit Type of Package 3 - S03 Number of Units in Package 3 - 50 Package 3 Height - 30 cm Package 3 Width - 30 cm Package 3 Length - 40 cm Package 3 Weight - 4.166 kg Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/intrerupator-cap-cruce-new-unica-10-a-alb-319132</div>
--	---