

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER INTRERUPATOR, NEW UNICA, 2 MODULE, IP44, ANTRACIT

Schneider Electric New Unica switch NU528254 is a in color anthracite. This is an IP44 switch with 2 modules. With IP44 level reached, the device has better performance against solid particle and liquid. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Switch

device presentation - Mechanism with fixing frame

Technology type - Electromechanical

Switch function - 1-pole 2-way

Number of rocker - 1

Device application - Light control

Provided equipment - Membrane

Colour tint - Anthracite (RAL 7021)

Type of packing - Flow-pack

Complementary

Rated current - 10 AX

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Electrical durability - 20000 cycles, cos phi = 0.6

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3

Condition of use - Indoor

Opening distance - > 3 mm

Actuator - Rocker

Connections - terminals - Screwless terminals

Cable cross section - 0.5-2.5 mm² rigid cable

0.5-2.5 mm² flexible cable

Material - ABS (acrylonitrile butadiene-styrene): mechanism cover

Marking - IP44

Surface finish - Matt

specific treatment - integrated within the material - Painted

Fixing mode - Screws or claws

Width - 74.5 mm

Height - 74.5 mm

Depth - 34.25 mm

Embedding depth - 21.15 mm

Net weight - 0.071 kg

Ambient air temperature for operation - -5 to +40 A°C

Ambient air temperature for storage - -5 to +50 A°C

Standards - EN 60669-1

LV directive

EMC directive

Product certifications - CE

AENOR

EAC

NF

VDE

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IP degree of protection - IP4X

IK degree of protection - IK04

Environmental characteristic - Alcohol

Window-cleaning fluid

Acetone

Petrol

UV resistant

Oil

Bleach

Liquid soap

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 3.5 cm

Package 1 Width - 7.5 cm
Package 1 Length - 7.5 cm
Package 1 Weight - 66.0 g
Unit Type of Package 2 - S02
Number of Units in Package 2 - 10
Package 2 Height - 15.0 cm
Package 2 Width - 30.0 cm
Package 2 Length - 40.0 cm
Package 2 Weight - 1080.0 g
Unit Type of Package 3 - P06
Number of Units in Package 3 - 160
Package 3 Height - 77.0 cm
Package 3 Width - 60.0 cm
Package 3 Length - 80.0 cm
Package 3 Weight - 25.78 kg
Pret: 42,86 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/intrerupator-new-unica-2-module-ip44-antracit-319164>