


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER PRIZA TELEFON, NEW UNICA, RJ12, 1 CONNECTSAU, 1 MODULE, BEJ**

Schneider Electric New Unica telephone socket NU349144 in color beige is a mechanism for data communication and with 1 module. The telephone socket type is RJ12. Its matching mounting box can be recessed into the surface of the wall with flush type. It is 22.5 mm in width, 45 mm in height, and 34 mm in depth. It reaches IP20 degree of protection too. Being environmentally friendly, this telephone socket is a green premium product too. And it is mercury free as well as heavy metal free, taking care of the environment and your health all the time. Being made of thermoplastic ABS-UV stabilised material, this telephone socket is quite reliable and resistant. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Telephone socket  
device presentation - Mechanism

Colour tint - Beige

Beige (RAL 1013)

Telephone socket type - RJ12 (6 contacts) - category 3 at 16 Mbit/s

Complementary

Socket number - 1

Number of modules - 1 module

Connections - terminals - Screw terminals twisted pair

Fixing mode - Clip-in

Material - ASA + PC: mechanism cover

ABS (acrylonitrile butadiene-styrene) GF10 FR: mechanism cover

Depth - 23 mm

Width - 22.5 mm

Height - 45 mm

Embedding depth - 12 mm

Net weight - 0.014 kg

Ambient air temperature for operation - -5a€;45 A°C

Ambient air temperature for storage - -5a€;45 A°C

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IP degree of protection - IP20

IK degree of protection - IK01

Environmental characteristic - Alcohol

Bleach

Petrol

Oil

Window-cleaning fluid

UV resistant

Liquid soap

Acetone

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 2.3 cm

Package 1 Width - 3.4 cm

Package 1 Length - 4.0 cm

Package 1 Weight - 13.0 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 10

Package 2 Height - 5.5 cm

Package 2 Width - 14.0 cm

Package 2 Length - 26.0 cm

Package 2 Weight - 227.0 g

Unit Type of Package 3 - S01

Number of Units in Package 3 - 20

Package 3 Height - 15.0 cm

Package 3 Width - 15.0 cm

Package 3 Length - 40.0 cm

Package 3 Weight - 654.0 g

Contractual warranty

Warranty - 18 months

Pret: 17,61 lei (TVA inclus)

