



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



SCHNEIDER NEW UNICA - PRIZA TELEFON - 1 X RJ11 - 2 M -**ALUMINIU**

Schneider Electric New Unica telephone socket NU549230 is a mechanism with fixing frame, mechanism with zamak fixing frame in color aluminium for data communication and with 2 modules. The telephone socket type is RJ11. Its matching mounting box can be recessed into the surface of the wall with flush type. It is 74.5 mm in width, 74.5 mm in height, and 34 mm in depth. The IP rating of this device is IP20. What's more, this device is qualified as a green premium product, with minimal use of hazardous substances. And it is mercury free and heavy metal free, which takes care of the environment and your health as always. Being made of thermoplastic ABS-UV stabilised, zamak material, this telephone socket is quite reliable and resistant. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Telephone socket

Device application - Communication

device presentation - Mechanism with fixing frame

Colour tint - Aluminium

Telephone socket type - RJ11 (4 contacts) - category 3 at 16 Mbit/s

Complementary Socket number - 1

Number of modules - 2 modules

Provided equipment - Fixing frame

Connections - terminals - Screw terminals twisted pair

device mounting - Flush

Fixing mode - Screws

Material - Zamak: fixing frame
Thermoplastic ABS-UV stabilised: central plate

Depth - 34 mm Width - 74.5 mm Height - 74.5 mm

Embedding depth - 25 mm

Ambient air temperature for operation - -25a€¦55 A°C Ambient air temperature for storage - -25a€¦55 A°C Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IP degree of protection - IP20

IK degree of protection - IK01

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 3.4 cm Package 1 Width - 7.5 cm Package 1 Length - 7.5 cm Package 1 Weight - 49 g

Unit Type of Package 2 - CAR

Number of Units in Package 2 - 4 Package 2 Height - 6 cm

Package 2 Width - 12 cm Package 2 Length - 17.5 cm

Package 2 Weight - 306 g Unit Type of Package 3 - S01

Number of Units in Package 3 - 16

Package 3 Height - 15 cm

Package 3 Width - 15 cm

Package 3 Length - 40 cm

Package 3 Weight - 1449 g Pret: 0,00 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/new-unica-priza-telefon-1-x-rj11-2-m-