Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



SCHNEIDER NEW UNICA - PRIZA TELEFON - 1 X RI11 - 2 M - BEI

Schneider Electric New Unica telephone socket NU549244 in color beige is a mechanism with fixing frame, mechanism with zamak fixing frame for data communication and with 2 modules. The telephone socket type is RJ11. Its matching mounting box can be recessed into the surface of the wall with flush type. It is 74.5 mm in width, 74.5 mm in height, and 34 mm in depth. It reaches IP20 degree of protection too. Being environmentally friendly, this telephone socket is a green premium product too. And it is mercury free and heavy metal free, which takes care of the environment and your health as always. The telephone socket is made of thermoplastic ABS-UV stabilised, zamak, making it as resistant as possible. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.Main

Range - New Unica

Product or component type - Telephone socket Device application - Communication

device presentation - Mechanism with fixing frame Colour tint - Beige (RAL 1013)

Telephone socket type - RJ11 (4 contacts) - category 3 at 16 Mbit/s

Complementary Socket number - 1

Number of modules - 2 modules

Provided equipment - Fixing frame

Connections - terminals - Screw terminals twisted pair

device mounting - Flush

Fixing mode - Screws

Material - Zamak: fixing frame
Thermoplastic ABS-UV stabilised: central plate

Depth - 34 mm Width - 74.5 mm Height - 74.5 mm

Embedding depth - 25 mm

Ambient air temperature for operation - -25a€¦55 A°C Ambient air temperature for storage - -25a€¦55 A°C Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IP degree of protection - IP20

IK degree of protection - IK01

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 3.4 cm Package 1 Width - 7.5 cm Package 1 Length - 7.5 cm

Package 1 Weight - 49 g Unit Type of Package 2 - CAR Number of Units in Package 2 - 4

Package 2 Height - 6 cm

Package 2 Width - 12 cm

Package 2 Length - 17.5 cm Package 2 Weight - 306 g Unit Type of Package 3 - S03

Number of Units in Package 3 - 64 Package 3 Height - 30 cm

Package 3 Width - 30 cm

Package 3 Length - 40 cm

Package 3 Weight - 4896 g Pret: 0,00 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/new-unica-priza-telefon-1-x-rj11-2-m-